

SELECTION OF SWITCH SETTINGS FOR MICRO-LUBER

Micro-Luber (60cc)

Lubricant output rates for various temperatures at altitudes from sea level to 1000 feet

Switch settings	+ 14° F		+ 32° F		+ 50° F		+ 68° F		+ 77° F		+ 86° F		+ 95° F		+ 113° F		+ 131° F	
	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty
All	3.00	20	3.40	18	3.85	16	4.25	14	4.45	13	4.70	13	4.90	12	5.30	11	5.55	11
1	1.40	43	1.60	38	1.80	33	2.00	30	2.10	29	2.20	27	2.30	26	2.50	24	2.60	23
2	0.70	86	0.80	75	0.90	67	1.00	60	1.05	57	1.10	55	1.15	52	1.25	48	1.30	46
3	0.45	133	0.55	109	0.60	100	0.67	90	0.70	86	0.75	80	0.75	80	0.85	71	0.85	69
6+12	0.35	171	0.40	150	0.45	133	0.50	120	0.55	109	0.55	109	0.60	100	0.65	92	0.65	92
6+B	0.30	200	0.35	171	0.40	150	0.45	133	0.45	133	0.50	120	0.50	120	0.55	109	0.60	100
6	0.25	240	0.25	240	0.30	200	0.34	179	0.35	171	0.35	171	0.40	150	0.40	150	0.45	133
12+B	0.20	300	0.20	300	0.25	240	0.25	240	0.25	240	0.30	200	0.30	200	0.30	200	0.35	171
12	0.10	600	0.15	400	0.15	400	0.17	364	0.15	400	0.20	300	0.20	300	0.20	300	0.20	300

Revised May 29, 2014

SELECTION OF SWITCH SETTINGS FOR MICRO-LUBER

Micro-Luber (60cc)

Lubricant output rates for various temperatures at altitudes from sea level to 1000 feet

Switch settings	+ 14° F		+ 32° F		+ 50° F		+ 68° F		+ 77° F		+ 86° F		+ 95° F		+ 113° F		+ 131° F	
	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty	Daily output cc's	Days until empty
All	3.00	20	3.40	18	3.85	16	4.25	14	4.45	13	4.70	13	4.90	12	5.30	11	5.55	11
1	1.40	43	1.60	38	1.80	33	2.00	30	2.10	29	2.20	27	2.30	26	2.50	24	2.60	23
2	0.70	86	0.80	75	0.90	67	1.00	60	1.05	57	1.10	55	1.15	52	1.25	48	1.30	46
3	0.45	133	0.55	109	0.60	100	0.67	90	0.70	86	0.75	80	0.75	80	0.85	71	0.85	69
6+12	0.35	171	0.40	150	0.45	133	0.50	120	0.55	109	0.55	109	0.60	100	0.65	92	0.65	92
6+B	0.30	200	0.35	171	0.40	150	0.45	133	0.45	133	0.50	120	0.50	120	0.55	109	0.60	100
6	0.25	240	0.25	240	0.30	200	0.34	179	0.35	171	0.35	171	0.40	150	0.40	150	0.45	133
12+B	0.20	300	0.20	300	0.25	240	0.25	240	0.25	240	0.30	200	0.30	200	0.30	200	0.35	171
12	0.10	600	0.15	400	0.15	400	0.17	364	0.15	400	0.20	300	0.20	300	0.20	300	0.20	300

Revised May 29, 2014